

TITAN

Dual Port Intelligent EV Charger

Unico
POWER

Charge two stalls for the cost of one install.

Shared charging gets expensive fast when every stall needs its own conduit run. TITAN serves two parking stalls from a single EV charger, with the conduit and materials of one. SuperMesh™ networking keeps every charger connected and install costs low, so you cover more of the building for less.

80 A

DUAL PORT

19.2 kW

PEAK OUTPUT



TITAN DUAL PORT EV CHARGER

Fastest Level 2 charging available

Twice the stalls, half the materials

Install one TITAN EV charger and serve two parking stalls with the conduit and labour of one. Save on materials and install time.

Fair charging for both stalls

Full power split ensures both vehicles charge, every time. Predictable overnight charging that keeps residents on equal footing.

Every vehicle, one station

TITAN offers both J1772 and NACS cables from the same unit. Every driver plugs in and charges, whatever they drive.

TITAN 80 A Dual Port Intelligent EV Charger



Get in touch today.

Talk to our team about your site: sales@unicopower.com

Electrical contractors: ask about certified installer pricing.



TITAN

Dual Port Intelligent EV Charger

Unico
POWER



TITAN dimensions (W × H × D)



One station, both connectors: J1772 and NACS

TITAN DUAL PORT EV CHARGER

Specifications

Enclosure Type	NEMA Type 4	Power Output	19.2 kW (240 VAC) / 16.6 kW (208 VAC)
Electrical Supply	208–240 VAC, single phase, 60 Hz (177–270 VAC)	Operating Temperature	–40 to +55°C ambient
Required Breaker	100 A, 2-pole @ 80 A output	Ventilation	Not required. Not for use with EVs requiring ventilation.
Output Current	80 A (40+40) or 64 A (32+32), software settable	Mounting	Wall, pedestal, ceiling
Power Sharing	Full split across both ports	Dimensions (W × H × D)	26 × 36 × 10 cm (10.3 × 14.2 × 3.9 in)
Failsafe Current	System settable, 0–7A	Weight	11.3 kg (25 lb) with standard cables
GFCI	CCID20, 20 mA	Safety & Certifications	ETL Listed (Intertek), Energy Star Certified
Charging Connector	SAE J1772 and NACS	Country of Origin	Made in China or Malaysia (tariff free under CPTPP)
Charging Cable	7.5 m (25 ft)	Communication	OCPP 1.6j
Smart Charging	OCPP 1.6j	Network	SuperMesh™ via Super Faro™ IoT Gateway (Wi-Fi, LoRa)

ORDERING

A-410802 — TITAN Dual Port EV Charger (80 A)

A-410482 — TITAN Dual Port EV Charger (48 A)

A-410402 — TITAN Dual Port EV Charger (40 A)

Unico
POWER